

This information was generated by the HP KEYMARK database on 17 Dec 2020

Summary of	F2120-20	Reg. No.	012-032
Certificate Holder			
Name	Nibe AB		
Address	Box 14	Zip	S-28521
City	Markaryd	Country	Sweden
Certification Body	RISE CERT		
Name of testing laboratory	DTI		
Subtype title	F2120-20		
Heat Pump Type	Outdoor Air/Water		
Refrigerant	R410a		
Mass Of Refrigerant	3 kg		
Certification Date	05.05.2020		

Model: F2120-20

General Data

Power supply	3x400V 50Hz
--------------	-------------

Heating

EN 14511-4

Operating range outdoor exchanger/indoor exchanger lower limit/lower limit	passed
Operating range outdoor exchanger/indoor exchanger upper limit/upper limit	passed
Shutting off the heat transfer medium flow	passed
Complete power supply failure	passed
Defrost test	passed

EN 14511-2

	Low temperature	Medium temperature
Heat output	6.94 kW	7.25 kW
El input	1.43 kW	2.35 kW
COP	4.85	3.08
Indoor water flow rate	1.20 m ³ /h	0.78 m ³ /h

Average Climate

This information was generated by the HP KEYMARK database on 17 Dec 2020

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	35 dB(A)	35 dB(A)
Sound power level outdoor	53 dB(A)	55 dB(A)

EN 14825		
	Low temperature	Medium temperature
η_s	199 %	153 %
Prated	11.00 kW	12.30 kW
SCOP	5.05	3.90
Tbiv	-7 °C	-7 °C
TOL	-10 °C	-10 °C
Pdh Tj = -7°C	9.74 kW	10.91 kW
COP Tj = -7°C	3.41	2.48
Pdh Tj = +2°C	6.47 kW	6.66 kW
COP Tj = +2°C	5.08	3.96
Pdh Tj = +7°C	6.86 kW	5.93 kW
COP Tj = +7°C	5.95	4.69
Pdh Tj = 12°C	6.76 kW	6.49 kW
COP Tj = 12°C	7.36	5.81
Pdh Tj = Tbiv	9.74 kW	10.91 kW

This information was generated by the HP KEYMARK database on 17 Dec 2020

COP Tj = Tbiv	3.41	2.48
Pdh Tj = TOL	10.80 kW	11.59 kW
COP Tj = TOL	3.11	2.40
Cdh	0.99	0.99
WTOL	65 °C	65 °C
Poff	25 W	25 W
PTO	7 W	12 W
PSB	25 W	25 W
PCK	37 W	37 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	0.20 kW	0.70 kW
Annual energy consumption Qhe	4508 kWh	6530 kWh

Colder Climate

EN 12102-1		
	Low temperature	Medium temperature
Sound power level indoor	35 dB(A)	35 dB(A)
Sound power level outdoor	53 dB(A)	53 dB(A)

EN 14825		
	Low temperature	Medium temperature

This information was generated by the HP KEYMARK database on 17 Dec 2020

η_s	165 %	134 %
Prated	13.00 kW	14.00 kW
SCOP	4.19	3.41
Tbiv	-12 °C	-12 °C
TOL	-22 °C	-22 °C
Pdh Tj = -7°C	7.87 kW	8.47 kW
COP Tj = -7°C	3.50	2.85
Pdh Tj = +2°C	6.20 kW	6.10 kW
COP Tj = +2°C	5.25	4.15
Pdh Tj = +7°C	5.90 kW	6.00 kW
COP Tj = +7°C	5.60	4.80
Pdh Tj = 12°C	6.70 kW	6.40 kW
COP Tj = 12°C	7.00	5.80
Pdh Tj = Tbiv	9.58 kW	10.32 kW
COP Tj = Tbiv	3.15	2.55
Pdh Tj = TOL	8.30 kW	8.69 kW
COP Tj = TOL	2.30	1.94
Cdh	0.99	0.99
WTOL	65 °C	65 °C
Poff	25 W	25 W
PTO	7 W	12 W

This information was generated by the HP KEYMARK database on 17 Dec 2020

PSB	25 W	25 W
PCK	35 W	35 W
Supplementary Heater: Type of energy input	Electricity	Electricity
Supplementary Heater: PSUP	4.70 kW	5.30 kW
Annual energy consumption Qhe	7639 kWh	10108 kWh